

MOSO® Bamboo X-treme® Outdoor Decking & Cladding accessories

MOSO® Fasteners

With these fasteners MOSO® Bamboo X-treme® Decking and Cladding can be easily installed. When installed correctly, there will be 5-6 mm gaps between the boards. The fasteners are supplied with matching stainless steel screws (square bit). For installation on aluminium sub frame joist (not provided by MOSO®), special screws are available.

Product Code	Item	Material	Colour	Dimensions fastener (mm)	Dimensions screw (mm)
CLIP-SCREW-BX08	Fastener Asymmetric with screw (20 mm)	Stainless steel A2 (AISI304)	Brown	27x22.5x10.8	4.5x30
CLIP-BX08	Fastener Asymmetric without screw (20 mm)	Stainless steel A2 (AISI304)	Brown	27x22.5x10.8	
CLIP-SCREW-BX801	Fastener Start/End Top with screw (20 mm)	Stainless steel A2 (AISI304)	Brown	29x25x11.2	4.5x30
CLIP-SCREW-BX09	Fastener Asymmetric with screw (18 mm)	Stainless steel A2 (AISI304)	Brown	27x22.5x9.8	4.5x30
CLIP-BX09	Fastener Asymmetric without screw (18 mm)	Stainless steel A2 (AISI304)	Brown	27x22.5x10.8	
SCREW-BX11-01	Screw for aluminium sub frame joist	Stainless steel S410 (AISI410)	Black*		4x20
CHEVRON-TOOL01	Chevron installation tool	Wood			



recommended number of fasteners/m²

decking*
137 mm board width
~20 pcs/m²

155 mm board width
~17 pcs/m²

178 mm board width
~14 pcs/m²

208 mm board width
~13 pcs/m²

cladding**
137 mm board width
~14 pcs/m²

75 mm board width
~26 pcs/m²

*) Based on distance of 462.5 mm between the sub frame joist centres.

**) Based on distance of 600 mm between the sub frame joist centres.

CLIP-SCREW-BX08 / BX09
CLIP-BX08 / BX09



CLIP-SCREW-BX801



SCREW-BX11-01

* Only black screw head



BO-SB155



BO-DTHT171G1-01/ BO-DTHT170G1



BO-DTHTBN171G-01



MOSO® Bamboo X-treme® additional products

The MOSO® Bamboo X-treme® additional products are made of the same material as the decking boards: Thermo-Density® heat-treated bamboo. MOSO® recommends the use of Bamboo X-treme® Sub frame joists, which are specifically produced for use in combination with MOSO® Decking. The MOSO® Bamboo X-treme® Fascia board and Edge profile are intended for an elegant finish of the sides of the decking. Fascia boards are installed vertically against the sides of the deck to cover the sub frame joists. Edge profiles can also be used to create stairs.

Product Code	Item	Finish	Dimensions (mm)
BO-SB155	Sub frame joist	Unfinished	2440x60x40
BO-DTHT170G1	Fascia board, 1 edge groove	Unfinished	1850x137x20
BO-DTHT171G1-01	Fascia board, 1 edge groove	Sikkens	1850x137x20
BO-DTHT181-01	Fascia board	Sikkens	1850x137x18
BO-DTHTBN171G-01	Edge profile, 2 edge grooves	Sikkens	1850x65x30/20

Maintenance & cleaning products

Under the influence of wind, rain, sun and snow the decking will weather. MOSO® recommends impregnating and maintaining the finished decking with Sikkens maintenance materials. It is recommended to finish the unfinished decking with Sikkens right after installation. The silicon carbide broom and machine disk are perfectly suited to clean and smooth the decking surface of Bamboo X-treme® and to remove splinters due to the capability to sand the surface in addition to cleaning it.

Product Code	Material
SEALER-05	Sealer for ends of boards 250 ml
DISK-01	16" Silicon carbide disk
BROOM-01	Silicon carbide broom
SATURATOR-SIK01	Sikkens Cetol WF 771 lpe colour 10 ltr
SATURATOR-SIK02	Sikkens Cetol WF 771 lpe colour 2.5 ltr